



www.xlam.biz

Xlam

XL1600 pro 2.0



main rolls \varnothing

130 mm

max. temperature

120 °C

up & down rolls

max. material thickness

30 mm


Plexiglass signal tower



Electro-pneumatic lifting



Included Blades Kit for trimming





XL1600 pro 2.0

PNEUMATIC HOT LAMINATOR WITH 2 ROLLERS UP TO 120°C

www.xlam.biz / info@xlam.biz

Unique features!

Cold roll-to-roll pneumatic laminator 1600 mm. Take-Up system included. **Two silicone rolls (heated) 130mm**, maximum temperature 120°C. Material thickness up to 30mm. **Trimming blades Included!**

Quick and easy to use, it allows you to save labor and improve productivity by increasing the quality of your work. Moreover, from today you can also laminate without liner with **"linerless" laminations**.

High efficiency

No crease or bubble, it guarantees excellent results even at temperatures below 120°C. **Equipped with footswitch feeding**, it allows the operator to keep both hands free for the rolling of wider supports.

Safety warranty

The **photocell sensor** prevents you place your hands near roll during the lamination. The emergency shutdown button is clearly visible on the front of the machine.

Product code

XL1600P2.0

Main silicon rolls diameter

130 mm

Packaging

anti-shock wooden

Maximum laminating film width

1600 mm

Main roll moving

by air compressor

Dimensions (l x h x p)

2000 x 1305 x 700 mm

Maximum material thickness

30 mm

Footswitch feeding

included

Packaging dimensions (l x h x p)

2250 X 740 x 840 mm

Maximum temperature

120 °C

Take-Up system

included

Machine / packaging weight

215 kg / 230 kg

Minimum-maximum speed

2,97 - 17,15 lmt/min

Heating method

internal with resistance

Safety

photocell / CE certification

Temperature-speed control


Micro Control

Maximum power / Voltage

4500 W / 220 v - 50 hz

Warranty

12 months



Authorized Reseller